

START SPOT ALU 870LM 3CCT DIM IP44 WHT
0005184



Produkteigenschaften

• Integrierter LED-Einbaustrahler. Vertikal schwenkbar 30°. Weißer Aluminiumrahmen. Phasenanschnitt-/Phasenabschnittdimmbar. 3-CCT umschaltbar 2.700-3.000-4.000 K. 50° Abstrahlwinkel. Gehäuse aus Polycarbonat und Aluminium. Geringe Einbautiefe 62 mm. IP44 von vorne. IK07. Loop-in/Loop-out-Klemmen für schnelle Verkabelung. 68 mm Ausschnitt. Klare Linse. Zusätzliche schwarze oder goldene Reflektoren können als Zubehör bestellt werden.

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	45	134.0	1.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	4	24.0	0.7	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	14	43.0	1.3	2.5 to 4.0	Excellent circularity
Overall performance	80.1	247.5	1.20		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
- Covering topics such as design for long life and repair
- Manufacturing :
- Additive and subtractive techniques and localisation
- Materials :
- Usage of recyclable materials rather than virgin
- Ecosystem :
- Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy

CIBSE (2021) Circular Economy Assessment Method - Make TM66 Digital Tool beta version 22nd October 2021 (London : Chartered Institution of Building Services Engineers)