

OBICO 68 IP65 530lm 3CCT DIM ADJ BRUSHED CHROME 0005365



Produkteigenschaften

- Integrierter LED-Einbaustrahler. 2-achsig verstellbar (horizontale Drehung 360°, vertikale Neigung 30°). Gebürstete Chromblende. 3 CCT-Optionen von 2.700-3000-4.000 K. Lichtstrom bis zu 550 lm. 5,4 W. Phasenanschnitt-/Phasenabschrittdimmbar. 38° Abstrahlwinkel. Gehäuse aus Aluminium und Stahl. Geringe Einbautiefe von 37 mm. Schutzart IP65. IK07. Loop-in/Loop-out-Klemmen für schnelle Verdrahtung. 68 mm Ausschnitt. Klare Linse. Luftdicht zur Begrenzung von Luftverlusten beim Einsatz in Wohngebäuden innerhalb der thermischen Hülle des Ge...

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Level
Product design	34	134.0	1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	2	24.0	0.3	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	70.1	247.5	1.10		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy