

OBICO 80 IP65 820LM 2CCT 930/940 DIM WHT
0005366



Produkteigenschaften

• Integrierter LED-Einbaustrahler. 2-achsig verstellbar (horizontale Drehung 360°, vertikale Neigung 30°). Farbe der Blende RAL9016 weiß. Zwei Lichttemperaturen wählbar: 3.000 K und 4.000 K. Lichtleistung 820 lm (4.000 K). 8,2 W. dimmbar. 38° Abstrahlwinkel. Gehäuse aus Aluminium und Stahl. Geringe Einbautiefe von 40 mm. Schutzart IP65. IK07. Loop-in-/Loop-out-Klemmen für schnelle Verkabelung. 80 mm Ausschnitt. Klare Linse. Luftdicht zur Begrenzung von Luftverlusten beim Einsatz in Wohngebäuden innerhalb der thermischen Hülle des Gebäud...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	34	134.0	1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	2	24.0	0.3	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	70.1	247.5	1.10		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy