



Produkteigenschaften

- Resisto, integrierte LED-Fluchtraumleuchte, mit UV-stabilisiertem Flachdiffusor, der für ein gleichmäßiges Lichtbild, eine optimale Systemeffizienz und eine Reduzierung der Blendung sorgt. Diffusorklemmen und Befestigungswinkel aus Edelstahl 301 für die Anbaumontage. Gehäuse und Diffusor aus Polycarbonat - keine Gelbverfärbung mit der Zeit. 2.800 lm. 20 W. 140 lm/W. 4.000 K. SDCM<5. CRI80. IP66. IK08 (Sensor IK03). Klasse I. 69.000 Stunden (L80B20) Lebensdauer. 1.288 x 87 x 80 mm. D-Zeichen. SylSmart Connected Building-fähig.

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Description
Product design	63.0	134.0	1.9	0.0 to 0.5	Very poor circular economy performance
Manufacturing	19.2	46.5	1.7	0.5 to 1.5	Some circular economy functionality
Materials	5.0	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17.0	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	104.2	247.5	1.50		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy