

Resisto 1500 HE IP66 7100lm 840 EM
0010272



Produkteigenschaften

• Resisto, integrierte wetterfeste LED-Leuchte mit UV-stabilisiertem Flachdiffusor, der für ein gleichmäßiges Lichtbild, eine optimale Systemeffizienz und weniger Blendung sorgt. Diffusorklemmen und Befestigungsbügel aus Edelstahl 301 für die Aufbaumontage. Gehäuse und Diffusor aus Polycarbonat - keine Gelbverfärbung mit der Zeit. 7100 lm; 50 W; 142 lm/W; 4.000 K; SDCM<3; nicht dimmbar; CRI80; IP66; IK08; Klasse I; 69.000 Stunden (L80B20) Lebensdauer; 1.500 mm x 89 mm x 88 mm; D-Zeichen; 3-Stunden-Notstrombatterien.

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	63.0	134.0	1.9	0.0 to 0.5	Very poor circular economy performance
Manufacturing	19.2	46.5	1.7	0.5 to 1.5	Some circular economy functionality
Materials	5.0	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17.0	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	104.2	247.5	1.50		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
- Covering topics such as design for long life and repair
- Manufacturing :
- Additive and subtractive techniques and localisation
- Materials :
- Usage of recyclable materials rather than virgin
- Ecosystem :
- Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy