

RESISTO 1500 HE IP66 4050-7100LM 840
0010331



Produkteigenschaften

• Resisto. Integrierte wetterfeste LED-Leuchte mit UV-stabilisiertem Flachdiffusor, der ein gleichmäßiges Lichtbild erzeugt, die Lichtleistung optimiert und Blendung reduziert. Diffusorklemmen und Befestigungswinkel aus Edelstahl 301 für die Anbaumontage. Gehäuse und Diffusor aus Polycarbonat - keine Gelbverfärbung mit der Zeit. 4.050-7.100 lm (über DIP-Schalter wählbar). 26,5-46 W. 153-157 lm/W. 4.000 K. SDCM<3. Nicht dimmbar. CRI80. IP66. IK08. Klasse I. Lebensdauer 69.000 Stunden (L80B20). 1.500 x 89 x 88 mm. D-Zeichen.

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	63.0	134.0	1.9	0.0 to 0.5	Very poor circular economy performance
Manufacturing	19.2	46.5	1.7	0.5 to 1.5	Some circular economy functionality
Materials	5.0	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17.0	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	104.2	247.5	1.50		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
- Covering topics such as design for long life and repair
- Manufacturing :
- Additive and subtractive techniques and localisation
- Materials :
- Usage of recyclable materials rather than virgin
- Ecosystem :
- Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy