

START SURFACE SLIM IP54 ROUND 1900LM 2CCT D WH 0043511



Produkteigenschaften

- Runde Decken-/Wandleuchte mit integrierter LED. Perfekte Lösung für Flure, Verkehrsflächen oder Bäder. Gleichmäßiges Licht in einem schlanken, aber robusten Design. Leistung 18 W. Lichtstrom 1.900 lm. Systemeffizienz 105 lm/W. Duale Farbtemperatur (3.000 K/4.000 K). Lieferung mit Phasendimmertreiber (Phasenan- und -abschnitt). Netzspannung 220-240 V~. Gehäusegröße: 280 mm Durchmesser x 53 mm Höhe. IK07. IP54 Schutzart. PC-Polycarbonat-Opal-Diffusor. Wartungsarm mit 58.000 Stunden LED-Lebenserwartung. Garantie: 5 Jahre.

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Description
Product design	70	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	4	24.0	0.7	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	109.1	247.5	1.50		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy