

START Surface Wall Cube IP54 2x140lm 2CCT Black 0047136



Produkteigenschaften

- Verstellbare Wandausleuchte für den Außenbereich, schwarzes Aluminium - RAL9005, 280 lm, 5,8 W, 48 lm/W, 3000/4.000 K schaltbare CCT, verstellbarer Ausstrahlungswinkel (0 - 94°), 104.000 Stunden Lebensdauer L70:B50, CRI 80, SDCM<3, IP54, IK05, 1000 Stunden Salzsprühetest, -20 - +45°C Betriebstemperaturbereich, 108x108x108 mm, Klasse I

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Description
Product design	39	134.0	1.2	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	3	24.0	0.5	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	77.1	247.5	1.23		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy