

Start Flood IP65 PIR 1000LM 840 Black 0050168



Produkteigenschaften

- Das stromlinienförmige, langlebige und leichte Aluminiumdruckgussgehäuse macht Start Flood IP65 zu einer perfekten Wahl für Gebäudefassaden, Parkplätze, Garagen und Baustellen. Das Produkt umfasst 1 m vorverdrahtetes abisoliertes Kabel und einen Montagebügel für eine schnelle und einfache Installation. Der universelle Montagebügel ermöglicht die Wand- oder Anbaumontage mit der Möglichkeit der vertikalen Neigung. Gehäuse schwarz (RAL9017). Weißer Reflektor. 1.000 lm. 10,5 W. 95 lm/W. 4.000 K. Nicht dimmbar. CRI>80. IP65. IK06. Klasse I...

CIBSE TM66

Result			
Category	Points Scored	Maximum possible points	Assessment
Product design	54.0	134.0	1.6
Manufacturing	17.1	46.5	1.5
Materials	4.0	24.0	0.7
Ecosystem	13.0	43.0	1.2
Overall performance	88.1	247.5	1.25

How to analyse the score	
0.0 to 0.5	Very poor circular economy performance
0.5 to 1.5	Some circular economy functionality
1.5 to 2.5	Definite/substantial progress to circularity
2.5 to 4.0	Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy