

SYLPIPE L600 950LM 840 HIGH OUTPUT 0090057



Produkteigenschaften

- LED-T5-Ersatzleiste, hohe Leistung: mehr Lumen pro Meter mit einer Effizienz von bis zu 125 Lumen/Watt, nahtlose Verbindung (bis zu 10 m), ideal für direkte Beleuchtung, z. B. unter Schränken oder in Küchen, Abstrahlwinkel von 120°, inkl. Schalter, inkl. 0,30 m abisoliertem Kabel, weißes Polycarbonatgehäuse, inkl. Standard- und Kipphalterungen

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Level
Product design	25	134.0	0.7	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	3	24.0	0.5	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	13	43.0	1.2	2.5 to 4.0	Excellent circularity
Overall performance	58.1	247.5	0.98		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy

CIBSE (2021) Circular Economy Assessment Method - Make TM66 Digital Tool beta version 22nd October 2021 (London : Chartered Institution of Building Services Engineers)