

OPTIX SURFACE 1200x200 2 LINE D/I 3000K ALU DALI 2023721



Produkteigenschaften

• OPTIX SURFACE 1200x200 2 LINE D/I 3.000 K ALU DALI ist eine hocheffiziente, blendfreie Leuchte für Büro- und Bildungsanwendungen. Direkte/indirekte Beleuchtung mit 80 % Downlight- und 20 % Uplight-Anteil für die abgehängte Deckenmontage. Größe: 1129x200x45 mm. Aluminisierte Kunststoffoptiken mit extra geringer Blendung in 2-Linien-Konfiguration. Weißer Leuchtenkörper RAL9016. DALI dimmbar. Warmweiße LED 3.000 K, CRI>80, Chromatizitätstoleranz der MacAdam-Ellipse in 3 Stufen. Lichtstrom 4.000 lm. Leistungsaufnahme 29 W. Systemeffizienz...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	76	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	23.4	46.5	2	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21	43.0	2	2.5 to 4.0	Excellent circularity
Overall performance	127.4	247.5	1.88		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy