



Produkteigenschaften

- OPTIX SURFACE 1200x200 2 LINE 4.000 K ALU SSA03 ist eine hocheffiziente, blendfreie Leuchte für Büro- und Bildungsanwendungen. Geeignet für Anbau- und Pendelmontage. Größe: 1.129 x 200 x 45 mm. Aluminisierte Kunststoffoptiken mit extra niedriger Blendung in 2-Linien-Konfiguration. Weißes Gehäuse in RAL9016. SylSmart Connected-fähig. Neutralweiße LED 4.000 K. CRI>80. Farbwerttoleranz der MacAdam-Ellipse mit 3 Stufen. Lichtstrom 3.600 lm. Leistungsaufnahme 27 W. Systemeffizienz 133 lm/W. Lebensdauer: 60.000 Stunden L90B10. UGR<16. Beleu...

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Description
Product design	76	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	23.4	46.5	2	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21	43.0	2	2.5 to 4.0	Excellent circularity
Overall performance	127.4	247.5	1.88		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy