

Features

- Insaver Slim is a ceiling recessed LED downlight (IP44 from the front), Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 9W; 1050lm; 117lm/W; 3000K; UGR <19 with shallow product depth 50mm. Meets TP(a) requirements.



CIBSE TM66

| Result | | | | How to analyse the score | |
|---------------------|---------------|-------------------------|------------|--------------------------|--|
| Category | Points Scored | Maximum possible points | Assessment | Score Range | Description |
| Product design | 60 | 134.0 | 1.8 | 0.0 to 0.5 | Very poor circular economy performance |
| Manufacturing | 17.1 | 46.5 | 1.5 | 0.5 to 1.5 | Some circular economy functionality |
| Materials | 0 | 24.0 | 0 | 1.5 to 2.5 | Definite/substantial progress to circularity |
| Ecosystem | 18 | 43.0 | 1.7 | 2.5 to 4.0 | Excellent circularity |
| Overall performance | 95.1 | 247.5 | 1.25 | | |

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy