

START Highbay IP65 10000-20000lm 2CCT WB 0039443



Features

- Integrated LED highbay, RAL9006 White aluminium housing, 11.100 / 15.700 / 19.800lm for 4000K or 10.900 / 15.600 / 19.500lm for 6500K, 72 / 110 / 150W depends on the settings of the integrated switch for changing the colour temperature (4000/6500K) and light output level, 132lm/W @ 150W 4000K setting, CRI 80; 110° beam angle, IP65, IK08, lifespan L70:B50 120.000 hrs; (D x H) 270 x 115 mm, D-mark.

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Performance Level
Product design	70	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	112.1	247.5	1.63		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy