



Features

- Integrated LED highbay; Black aluminium housing; 13000Lm; 80 W; 163 Lm/W; 4000K; Drive current: 410mA; CRI 80; 55° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

CIBSE TM66

| Result | | | | How to analyse the score | |
|---------------------|---------------|-------------------------|------------|--------------------------|--|
| Category | Points Scored | Maximum possible points | Assessment | Score Range | Description |
| Product design | 76.0 | 134.0 | 2.3 | 0.0 to 0.5 | Very poor circular economy performance |
| Manufacturing | 17.1 | 46.5 | 1.5 | 0.5 to 1.5 | Some circular economy functionality |
| Materials | 4.0 | 24.0 | 0.7 | 1.5 to 2.5 | Definite/substantial progress to circularity |
| Ecosystem | 18 | 43.0 | 1.7 | 2.5 to 4.0 | Excellent circularity |
| Overall performance | 115.1 | 247.5 | 1.55 | | |

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy