

OTAO LINEAR CORN-X OPAL 830/840 WH **0041811**



Features

• X-shape connection unit for opal diffuser version of Otao Linear range, RAL9003 (white) finishing, direct distribution, only 3000K/4000K LED light sources included, feed by next straight luminaire, shipped with 4x fast connectors and additional replacement electrical connectors, 50mm wide extruded aluminium profile, nominal size: 290x290x50x73mm.

CIBSE TM66

Result				
Category	Points Scored	Maximum possible points	Assessment	
Category	Points Scored	waxiiiuiii possible poiitis	Assessment	
Product design	80	134.0	2.4	
Manufacturing	20.1	46.5	1.7	
Materials	4	24.0	0.7	
Ecosystem	30	43.0	2.8	
Overall performance	134.1	247.5	1.90	

How to analyse the score		
0.0 to 0.5	Very poor circular economy performance	
0.5 to 1.5	Some circular economy functionality	
1.5 to 2.5	Definite/substantial progress to circularity	
2.5 to 4.0	Excellent circularity	

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what it's practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections:

Product Design: Covering topics such as design for long life and repair

Manufacturing: Additive and subtractive techniques and localisation

Materials: Usage of recyclable materials rather than virgin

Ecosystem: Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy

CIBSE (2021) Circular Economy Assessment Method - Make TM66 Digital Tool beta version 22nd October 2021 (London: Chartered Institution of Building Services Engineers)