

Features

• Insaвер is a ceiling recessed LED downlight (IP44 from the front), Die-cast aluminium body, loop in loop out connector for quick installation, Dimmable DALI driver of TRIDONIC (LCA 17W 250–700mA one4all SR PRE 28000670), 13W; 1700lm; 131lm/W; 4000K; UGR <19 with shallow product depth 60mm. Meets TP(a) requirements.


Product Overview

Product name	INSAVER U19 IP44 175 1700LM 840 DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
ETIM Class	EC001744
E-number FI	4278516
Fixture luminous flux (lm)	1700
Luminaire efficacy (lm/W)	131
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	70
Beam Angle (°)	NA
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	13
Electrical protection	Class II

INSAVER U19 IP44 175 1700LM 840 DALI 0030537

Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL9010
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288305370
Warranty	5 years
Dimming method	DALI-2, Switch-dim (mains-rated)
Colour Code	840
Useful luminous flux (#use)	1700

Photometry



Technical drawings

