


START Panel UGR19 600x600 3600Lm 840 LILO  
0042184



Features

- START Panel is a range of backlit LED panels used in recessed ceilings. Ideal for general indoor applications such as corridors, breakrooms, offices and meeting rooms. Luminaire dimensions are compatible with common ceiling installation, and the shallow design makes it easy to install in low ceilings. 3600Lm; 36W; 100Lm/W; Drive current: 750mA; Average lifespan: 100.000Hrs; 4000K;CRI 80; Glare control <19; IK03; IP40 (from the front); SDCM<3; Class II; Loop in loop out connector for quick installation.


Product Overview

|                                   |   |
|-----------------------------------|---|
| Product name                      | START Panel UGR19 600x600 3600Lm 840 LILO |
| Technology                        | LED                                       |
| Housing                           | Aluminium, Steel                          |
| Mount                             | Ceiling recessed mounting                 |
| General application               | Education, Office                         |
| ETIM Class                        | EC002892                                  |
| E-number FI                       | 4278355                                   |
| Fixture luminous flux (lm)        | 3600                                      |
| Luminaire efficacy (lm/W)         | 100                                       |
| Correlated colour temperature (k) | 4000                                      |
| Light colour                      | Neutral White                             |
| CRI (Ra)                          | 80  |
| Colour Variation Initial (SDCM)   | 3   |
| Beam Angle (°)                    | 90  |
| Glare control                     | < 19                                      |
| Photobiological Risk Group        | RG0                                       |
| Total power consumption (W)       | 36  |
| Electrical protection             | Class II                                  |
| Control gear type                 | LED driver constant current               |

START Panel UGR19 600x600 3600Lm 840 LILO  
0042184

|                     |                        |
|---------------------|------------------------|
| Dimmable            | No                     |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour      | RAL9003                |
| IP rating           | IP40/20                |
| IK rating           | IK03                   |
| Product EAN number  | 5410288421841          |
| Warranty            | 5 years                |
| Dimming method      | N/A                    |

Photometry



Technical drawings

