

Quantum IP54 600x600 Multipower 4300lm 830 0044658















Features

 Quantum is a range of recessed integrated LED panels for general indoor lighting applications such as breakout areas, offices and meeting rooms. With the help of DIP Switch multiple lumen outputs can be set up in 4 steps (22W 3200lm, 24W 3550lm, 26W 3900lm, 28W 4300lm). Max. drive current: 600mA; Lifespan: 120.000Hrs L70:B50; 3000K; CRI 80; Efficacy up to: 154Lm/W; Glare control <19; IK03; IP54 (from the front); Class II; Tp(a) rated diffuser that self-estinguishes within 5 sec when a flame has been removed.

Product Overview


| Product name | Quantum IP54 600x600 Multipower 4300lm 830 |
|-----------------------------------|--|
| Technology | LED |
| Cap/Base | N/A |
| Housing | Steel |
| Mount | Ceiling recessed mounting |
| General application | Education, Office |
| ETIM Class | EC002892 |
| E-number FI | 4279425 |
| Fixture luminous flux (lm) | 4300 |
| Luminaire efficacy (lm/W) | 154 |
| Correlated colour temperature (k) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 3 |
| Beam Angle (°) | 85 |
| Glare control | < 19 |
| Photobiological Risk Group | RG0 |
| Total power consumption (W) | 28 |



Quantum IP54 600x600 Multipower 4300lm 830 **0044658**

| Electrical protection | Class II |
|-----------------------|-----------------------------|
| Control gear type | LED driver constant current |
| Dimmable | No |
| LED Flickering Rate | Ultra low (5% or less) |
| Housing colour | RAL9003 |
| IP rating | IP54/20 |
| IK rating | IK03 |
| Product EAN number | 5410288446585 |
| Warranty | 5 years |
| Dimming method | N/A |

Photometry



Technical drawings

