

QUADRO 600x600 840 DALI 0044703















Features

 QUADRO 600x600 840 DALI Unique stylish recessed modular LED luminaire, ideal for general indoor lighting applications such as breakout areas, offices and meeting rooms. Steel frame with integrated reflector, passive cooling. Low glaring UGR<16. RG1, 75° beam angle, optical system: white painted reflector with total internal reflection lenses. Light color temperature: 4000K (Neutral White), max system power: 34W (900mA), max fixture output: 4650lm, efficacy at max output 137lm/W, max efficacy 153lm/W @ 15W, CRi (Ra) >80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), lifespan: 88,000 hours at 80% of the original output (L80B20), IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, low flicker, SELV DALI driver, electrical protection: Class II. Ingress protection IP40/IP20, suitable for indoor environment only. Nominal size: 595x595mm, Loop in / loop out wiring, saftey cables included, 18mm nominal height, RAL 9003 - Signal white color frame, weight: 3,20kg.

Product Overview


Product name	QUADRO 600x600 840 DALI
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting, Suspended
General application	Office, Education
ETIM Class	EC002892
E-number FI	4279449
Fixture luminous flux (Im)	4650
Luminaire efficacy (lm/W)	137



QUADRO 600x600 840 DALI **0044703**

ht colour N	Neutral White
(Ra) 8	30
our Variation Initial (SDCM) 3	
nm Angle (°)	75
re control <	: 16
otobiological Risk Group	RG1
al power consumption (W) 3	34
ctrical protection C	Class II
ntrol gear type	Electronic ballast multiwatt
nmable Y	'es
O Flickering Rate	Jltra low (5% or less)
using colour R	RAL9003
ating IF	P40/20
ating Il	K08
duct EAN number 5	3410288447032
rranty 5	years
It in presence detector	IONE
ual assistant compatibility N	I/A
nming method	DALI-2

Photometry



Technical drawings

