



Features

- OPTICLIP R 625 840 2L WHT SSA03 is a high efficacy low glare ceiling recessed mounted luminaire with replaceable light engines for office and education applications. White colour plastic optic (reflector + lens), direct light distribution. Luminaire dimensions: 620x620x44mm. White body colour (RAL9016), IP40 (from the front), IK07, SylSmart Connected enabled with integrated sensor, 33.5W power consumption, 4000K (neutral white) CCT, 4700lm luminous flux at 900mA drive current level, 140lm/W system efficacy, CRI>80, SDCM≤3 (3-step Mac...

CIBSE TM66

Result				How to analyse the score
Category	Points Scored	Maximum possible points	Assessment	
Product design	90	134.0	2.7	0.0 to 0.5 Very poor circular economy performance
Manufacturing	24.2	46.5	2.1	0.5 to 1.5 Some circular economy functionality
Materials	6	24.0	1	1.5 to 2.5 Definite/substantial progress to circularity
Ecosystem	34	43.0	3.2	2.5 to 4.0 Excellent circularity
Overall performance	154.2	247.5	2.25	

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

Product Design : Covering topics such as design for long life and repair

Manufacturing : Additive and subtractive techniques and localisation

Materials : Usage of recyclable materials rather than virgin

Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy