



Features

- AREUM WALL 600 D/I 4000K ALU DALI is a highly efficient wall mounted LED luminaire with 40% direct and 60% indirect light distribution. 28mm high aluminium body with rounded edges. Length 600mm, width 200mm. White aluminium RAL9006 powder coated luminaire body and powder coated steel wall mounted gearbox. Low flicker (<5%) DALI dimmable driver. Luminous flux: 5850lm, Power consumption: 45W. Luminaire efficacy: 130lm/W. CRI (Ra)>80 4000K (Neutral White) LED, chromaticity tolerance: SDCM<3. Lifespan: L80B10 100,000h. UGR<16, Luminance at...

CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	0.0 to 0.5	Very poor circular economy performance
Product design	59	134.0	1.8	0.5 to 1.5	Some circular economy functionality
Manufacturing	17.1	46.5	1.5	1.5 to 2.5	Definite/substantial progress to circularity
Materials	4	24.0	0.7	2.5 to 4.0	Excellent circularity
Ecosystem	18	43.0	1.7		
Overall performance	98.1	247.5	1.43		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

Product Design : Covering topics such as design for long life and repair
Manufacturing : Additive and subtractive techniques and localisation
Materials : Usage of recyclable materials rather than virgin
Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy