



Features

- The streamlined, durable, lightweight die-cast aluminium body makes SylFlood a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. White (RAL9003) housing, white reflector, 3000 lm, 26 W, 115 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, 112 x 125 x 26 mm (L x W x H). Weight: 0.325 kg.

CIBSE TM66

Result				How to analyse the score
Category	Points Scored	Maximum possible points	Assessment	
Product design	54.0	134.0	1.6	0.0 to 0.5 Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5 Some circular economy functionality
Materials	4.0	24.0	0.7	1.5 to 2.5 Definite/substantial progress to circularity
Ecosystem	13.0	43.0	1.2	2.5 to 4.0 Excellent circularity
Overall performance	88.1	247.5	1.25	

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

Product Design : Covering topics such as design for long life and repair
Manufacturing : Additive and subtractive techniques and localisation
Materials : Usage of recyclable materials rather than virgin
Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy