

Solstice 200 3280 930 DALI Pendant Direct/Indirect 2070215



Features

- The Solstice 200 3280 930 DALI Pendant Direct/Indirect is a high efficient DALI dimmable downlight luminaire with direct (2700lm) and indirect (580lm) light distribution, Colour rendering index Ra>90, Colour temperature: 3000K Warm White, Class II, Overall dimensions: dia 196mm, height 196mm.

CIBSE TM66

Result				
Category	Points Scored	Maximum possible points	Assessment	
Product design	75	134.0	2.2	
Manufacturing	18.7	46.5	1.6	
Materials	4	24.0	0.7	
Ecosystem	19	43.0	1.8	
Overall performance	116.7	247.5	1.58	
				How to analyse the score
				0.0 to 0.5 Very poor circular economy performance
				0.5 to 1.5 Some circular economy functionality
				1.5 to 2.5 Definite/substantial progress to circularity
				2.5 to 4.0 Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy

CIBSE (2021) Circular Economy Assessment Method - Make TM66 Digital Tool beta version 22nd October 2021 (London : Chartered Institution of Building Services Engineers)