



Caractéristiques de la gamme

- Integrated LED recessed spotlight, vertical tilt 30°, black aluminium bezel finish, dimmable trailing/leading edge, 3-CCT changeable 2700-3000-4000K, 50° degree beam angle, polycarbonate and aluminium body, low profile 62mm recessed depth, IP44 from the front, IK07, loop-in/loop-out terminals for fast wiring, 68mm cutout, clear lens. Additional white or gold reflectors can be ordered as accessory.

CIBSE TM66

| Result | | | | How to analyse the score | |
|---------------------|---------------|-------------------------|------------|--------------------------|--|
| Category | Points Scored | Maximum possible points | Assessment | Score Range | Performance Level |
| Product design | 45 | 134.0 | 1.3 | 0.0 to 0.5 | Very poor circular economy performance |
| Manufacturing | 17.1 | 46.5 | 1.5 | 0.5 to 1.5 | Some circular economy functionality |
| Materials | 4 | 24.0 | 0.7 | 1.5 to 2.5 | Definite/substantial progress to circularity |
| Ecosystem | 14 | 43.0 | 1.3 | 2.5 to 4.0 | Excellent circularity |
| Overall performance | 80.1 | 247.5 | 1.20 | | |

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy