

Pixo Line 1500 UGR19 50W 2700-7300lm 830 Blanc
0007825



Caractéristiques de la gamme

- Pixo Line luminaire linéaire modulaire, simple d'installation offrant un éclairage d'une grande flexibilité d'utilisation. Installation facile en deux modules (led et driver) séparés. Mécanisme Push-in/push-out avec connecteur GR6d-15. Compatible avec Zhaga Book 14. Corps aluminium et embouts plastique. Optique à faible éblouissement UGR19, angle du faisceau lumineux de 70°. Finition blanc texturé. Température de couleur 3000K. Puissance max. 50W. Rendement lumineux max. : 7300lm. Efficacité : 146lm/W. Ra80 typique. Très bonne homogénéité.

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	61	134.0	1.8	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	6	24.0	1	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21	43.0	2	2.5 to 4.0	Excellent circularity
Overall performance	105.1	247.5	1.58		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy