



### Caractéristiques de la gamme

- Resisto 600 IP66 12W 1600lm 865 - Solution étanche Led en polycarbonate. Étriers coulissants en inox 301 et platine LED fixée à la vasque. Pré-perçage aux extrémités pour 1 ou 2 presse-étoupes. Température de couleur 6500K, IRC80. Flux lumineux sortant 1600lm. Puissance consommée 12W. Efficacité lumineuse : 133lm/W. Facteur de puissance : 0,95. Taux de distorsion harmonique : 20%. Durée de vie (L80) : 69.000h. Risque photobiologique RG1, IP66, IK08. Test au fil incandescent 850°C. Températures de fonctionnement de -20°C à 40°C. Class...

### CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Description
Product design	63.0	134.0	1.9	0.0 to 0.5	Very poor circular economy performance
Manufacturing	19.2	46.5	1.7	0.5 to 1.5	Some circular economy functionality
Materials	5.0	24.0	0.8	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	17.0	43.0	1.6	2.5 to 4.0	Excellent circularity
Overall performance	104.2	247.5	1.50		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy