

OptiClip 1200 1L 34W 4450lm 830 Blanc SSAD
0034019



Caractéristiques de la gamme

• Luminaire architectural à modules LED interchangeable. Solution éco-responsable avec modules LED et driver remplaçables. Version gestion d'éclairage intelligente SylSmart Connected sans capteur. Flux lumineux max 4450lm. Puissance max 34W. Efficacité jusqu'à 135lm/W. Température de couleur 3000K. IRC>80. Faible éblouissement UGR<19. Dimensions : 1195x295x34mm. Finition blanche (RAL9016). IP40. IK07. Classe II. Certification ENEC. Bornier de repiquage LiLo. Durée de vie 100 000h (L80B20). Garantie 5 ans.

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	90	134.0	2.7	0.0 to 0.5	Very poor circular economy performance
Manufacturing	24.2	46.5	2.1	0.5 to 1.5	Some circular economy functionality
Materials	6	24.0	1	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	34	43.0	3.2	2.5 to 4.0	Excellent circularity
Overall performance	154.2	247.5	2.25		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what it's practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy