

START Batten 1200 20/35W 3000/5000lm 830/840
0048978



Caractéristiques de la gamme

• START Batten 1200 20/35W 3000/5000lm 830/840 - Réglette Led en polycarbonate multipuissance et double CCT par sélecteurs. Pré-perçage aux extrémités pour câblage. Double température de couleur 3000/4000K, IRC80. Flux lumineux sortant 3000/5000lm. Puissance consommée 20,5/35,5W. Efficacité lumineuse : 141lm/W. Facteur de puissance : 0,9. Taux de distorsion harmonique : 20%. Durée de vie (L70) : 100 000h. Risque photobiologique GR1, IP20, IK08. Test au fil incandescent 650°C. Températures de fonctionnement de -20°C à 40°C. Classe I. Dri...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	71	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	113.1	247.5	1.63		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy