

## KubiXx IP65 L6 188W 32000lm 840 Allée DALI 0062126



### Caractéristiques de la gamme

- KubiXx IP65 L6 188W 32000lm 840 Allée DALI - Armature industrielle LED haute efficacité destinée à l'éclairage de grande hauteur. Corps acier. Température de couleur (CCT) 4000K. IRC>80. Distribution lumineuse à 30x60°. Flux lumineux sortant 32500lm. Puissance consommée 188W. Efficacité lumineuse 172lm/W. Facteur de puissance 0,98. Maintien du flux de L80: 95.000h. Gestion DALI. Groupe de risque photobiologique GR1. IP65. IK06. Classe I. Compatible régimes de neutre IT, TT et TN. 850°C. Température de fonctionnement de -40°C à +50°C. ...

### CIBSE TM66

Result				How to analyse the score	
Category	Points Scored	Maximum possible points	Assessment	Score Range	Description
Product design	69.0	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	20.6	46.5	1.8	0.5 to 1.5	Some circular economy functionality
Materials	8.0	24.0	1.3	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21.0	43.0	2.0	2.5 to 4.0	Excellent circularity
Overall performance	118.6	247.5	1.80		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy