

KubiXx IP65 L3 83W 14000lm 840 Allée SSA N
0062162



Caractéristiques de la gamme

• KubiXx IP65 L3 83W 14000lm 840 Allée SSA N - Armature industrielle LED haute efficacité destinée à l'éclairage de grande hauteur. Corps acier. Température de couleur (CCT) 4000K. IRC>80. Distribution lumineuse à 30x60°. Flux lumineux sortant 14400lm. Puissance consommée 83W. Efficacité lumineuse 173lm/W. Facteur de puissance 0,98. Maintien du flux de L80: 95.000h. Système de gestion SylSmart Connected "N" en noeud de commande sans capteur PIR. Groupe de risque photobiologique GR1. IP65. IK06. Classe I. Compatible régimes de neutre IT,...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	69.0	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	20.6	46.5	1.8	0.5 to 1.5	Some circular economy functionality
Materials	8.0	24.0	1.3	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21.0	43.0	2.0	2.5 to 4.0	Excellent circularity
Overall performance	118.6	247.5	1.80		

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what it's practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy