

SylSpot 500lm 830 IP65 Blanc Pack de 3  
0090022



Caractéristiques de la gamme

• Spot d'accentuation LED offrant une grande efficacité lumineuse. Version IP44 orientable ou IP65 fixe. Angle de faisceau 38°. Flux lumineux 500-550lm, efficacité lumineuse 100-104lm/W. Versions dimmables ou non-dimmables. Température de couleur : blanc chaud (3000K), blanc neutre (4000K) ou 3-CCT (2700/3000/4000K sélectionnables sur le driver). IRC80. Hauteur 47mm, diamètre d'encastrement 68-74mm. Bornier repiquable LILO. Versions blanches (inclus une collerette supplémentaire argentée à clipser) ou noires. Durée de vie 57 000 heures ...

CIBSE TM66

| Result              |               |                         |            |                                              |
|---------------------|---------------|-------------------------|------------|----------------------------------------------|
|                     |               |                         |            |                                              |
| Category            | Points Scored | Maximum possible points | Assessment |                                              |
| Product design      | 27            | 134.0                   | 0.8        |                                              |
| Manufacturing       | 17.1          | 46.5                    | 1.5        |                                              |
| Materials           | 3             | 24.0                    | 0.5        |                                              |
| Ecosystem           | 13            | 43.0                    | 1.2        |                                              |
| Overall performance | 60.1          | 247.5                   | 1.00       |                                              |
|                     |               |                         |            | How to analyse the score                     |
|                     |               |                         |            | 0.0 to 0.5                                   |
|                     |               |                         |            | Very poor circular economy performance       |
|                     |               |                         |            | 0.5 to 1.5                                   |
|                     |               |                         |            | Some circular economy functionality          |
|                     |               |                         |            | 1.5 to 2.5                                   |
|                     |               |                         |            | Definite/substantial progress to circularity |
|                     |               |                         |            | 2.5 to 4.0                                   |
|                     |               |                         |            | Excellent circularity                        |

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what it's practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :  
Manufacturing :  
Materials :  
Ecosystem :
- Covering topics such as design for long life and repair  
Additive and subtractive techniques and localisation  
Usage of recyclable materials rather than virgin  
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy