



Caractéristiques de la gamme

• OPTIX S 1200 2L HO 36W 5100lm 830 D/I ALU DALI - luminaire suspendu à haute efficacité et à faible éblouissement pour les applications tertiaires. Distribution directe/indirecte (70/30%) pour un confort accru. Optique à très faible luminance en polycarbonate finition aluminisée dans une configuration à 2 lignes. Driver DALI certifié ENEC dimmable jusque 1%. Très faible scintillement <5%. Température de couleur (CCT)3000K, IRC>80, consistance des couleurs SDCM<3. Flux lumineux sortant 5100 lm. Puissance consommée 36W. Efficacité lumine...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	76	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	23.4	46.5	2	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21	43.0	2	2.5 to 4.0	Excellent circularity
Overall performance	127.4	247.5	1.88		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy