


START Downlight 5in1 65-260 2300LM 0053151



Features

- START Downlight 5in1 is an integrated LED recessed / surface mounted downlight with built in non dimmable driver. Colour temperature (3000K, 4000K and 6500K) can be adjusted by a 3-way switch located on the back of the fixture. Adaptability to various cut-outs from 65mm to 260mm

CIBSE TM66

| Result | | | | How to analyse the score | |
|---------------------|---------------|-------------------------|------------|--------------------------|--|
| Category | Points Scored | Maximum possible points | Assessment | Score Range | Description |
| Product design | 41 | 134.0 | 1.2 | 0.0 to 0.5 | Very poor circular economy performance |
| Manufacturing | 17.1 | 46.5 | 1.5 | 0.5 to 1.5 | Some circular economy functionality |
| Materials | 2 | 24.0 | 0.3 | 1.5 to 2.5 | Definite/substantial progress to circularity |
| Ecosystem | 15 | 43.0 | 1.4 | 2.5 to 4.0 | Excellent circularity |
| Overall performance | 75.1 | 247.5 | 1.10 | | |

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what its practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assessment Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which ask for back-up evidence, is split into four sections :

- Product Design : Covering topics such as design for long life and repair
- Manufacturing : Additive and subtractive techniques and localisation
- Materials : Usage of recyclable materials rather than virgin
- Ecosystem : Repair or upgrade services to complement circular economy design

The outcome of the assessment is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy