



Productkenmerken

• OPTIX S 1200 2L 29W 4100lm 840 D/I ALU - zeer efficiënte, laagluminantie pendelarmatuur voor commerciële toepassingen. Distribution directe/indirecte (70/30%) voor un confort accru. Zeer lage luminantie polycarbonaat optiek met gealuminiseerde afwerking in een 2-lijns configuratie. Armatuur kan bedekt worden met glaswol of akoestische isolatie. Driver ENEC gecertificeerd. Zeer lage flikkering <5%. Kleurtemperatuur (CCT) 4000K, CRI>80, kleurconsistentie SDCM<3. Lichtstroom 4100 lm. Vermogen 29W. Rendement 141 lm/W. Lumenbehoud L80>107 ...

CIBSE TM66

Result				
Category	Points Scored	Maximum possible points	Assessment	
Product design	76	134.0	2.3	
Manufacturing	23.4	46.5	2	
Materials	7	24.0	1.2	
Ecosystem	21	43.0	2	
Overall performance	127.4	247.5	1.88	

How to analyse the score	
0.0 to 0.5	Very poor circular economy performance
0.5 to 1.5	Some circular economy functionality
1.5 to 2.5	Definite/substantial progress to circularity
2.5 to 4.0	Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy's main aims, how it can be achieved and what it's practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)'s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product's performance in the context of a Circular Economy