

Resisto 1200 IP65 2800lm 840 SSC S
0010228



Productkenmerken

• Resisto 1200 IP66 23W 2800lm 840 SSC PIR - Led waterdicht armatuur in polycarbonaat. Schuifbeugels in roestvrij staal 301 en platine bevestigd aan de behuizing. Uitbreekpoorten aan de uiteinden voor 1 of 2 wartels en centraal voor voeding vanuit het midden. Kleurtemperatuur 4000K, CRI80. Lichtstroom 2800lm. Vermogen 23W. Rendement : 121lm/W. Powerfactor : 0,95. Harmonische vervorming: 20%. Verwachte levensduur (L80) : 69.000u. SylSmart Standalone Bluetooth lichtsturingssysteem. Ingebouwde PIR-sensor. Fotobiologische risicogroep RG1, l...

CIBSE TM66

Result				
Category	Points Scored	Maximum possible points	Assessment	
Product design	63.0	134.0	1.9	
Manufacturing	19.2	46.5	1.7	
Materials	5.0	24.0	0.8	
Ecosystem	17.0	43.0	1.6	
Overall performance	104.2	247.5	1.50	
				How to analyse the score
				0.0 to 0.5
				Very poor circular economy performance
				0.5 to 1.5
				Some circular economy functionality
				1.5 to 2.5
				Definite/substantial progress to circularity
				2.5 to 4.0
				Excellent circularity

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy