

START Batten 1800 5000/9000lm 830/840
0048980



Productkenmerken

• START Batten 1800 33/68W 5000/9000lm 830/840 - LED-armatuur van polycarbonaat met meerdere vermogens en dubbele CCT-keuzeschakelaars. Voorgeboorde uiteinden voor bedrading. Dubbele kleurtemperatuur 3000/4000K, CRI80. Uitgangslichtstroom 5000/9000lm. Energieverbruik 33/68W. Lichtrendement: 135lm/W. Vermogensfactor: 0,9. Harmonische vervorming: 20%. Levensduur (L70): 120.000 uur. Fotobiologisch risico GR1, IP20, IK08. Gloeidraadtest 650°C. Bedrijfstemperaturen van -20°C tot 40°C. Klasse I. Niet-dimbare driver. Optionele MW On/Off bewegi...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	71	134.0	2.1	0.0 to 0.5	Very poor circular economy performance
Manufacturing	17.1	46.5	1.5	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	18	43.0	1.7	2.5 to 4.0	Excellent circularity
Overall performance	113.1	247.5	1.63		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy