

OPTIX RECESSED 1200x300 2L 4000K ALU DALI
2023665



Productkenmerken

• OPTIX E 1200 2L 26W 3600lm 840 ALU DALI - zeer efficiënte, niet-verblindende inbouwarmatuur voor commerciële toepassingen. Zeer lage luminantie polycarbonaat optiek met gealuminiseerde afwerking in een 2-lijns configuratie. Armatuur kan bedekt worden met glaswol of akoestische isolatie. DALI dimbaar tot 1%. Zeer lage flikkering <5%. Kleurtemperatuur (CCT) 4000K, CRI>80, kleurconsistentie SDCM<3. Lichtstroom 3600 lm. Vermogen 26W. Rendement 138 lm/W. Lumenbehoud L80>107 500h. UGR<16 en lage luminantie<200 Cd/m² bij 65° geschikt voor w...

CIBSE TM66

Result					
Category	Points Scored	Maximum possible points	Assessment	How to analyse the score	
Product design	76	134.0	2.3	0.0 to 0.5	Very poor circular economy performance
Manufacturing	23.4	46.5	2	0.5 to 1.5	Some circular economy functionality
Materials	7	24.0	1.2	1.5 to 2.5	Definite/substantial progress to circularity
Ecosystem	21	43.0	2	2.5 to 4.0	Excellent circularity
Overall performance	127.4	247.5	1.88		

Technical Memorandum (TM) 66 describes a Circular Economy’s main aims, how it can be achieved and what it’s practice will mean to the different branches of our industry like specifiers, manufacturers, contractors, and Facilities Managers.

The Circular Economy Assement Method for Manufacturing (CEAM-Make)’s list of 66 searching questions, the majority of which askfor back-up evidence, is split into four sections :

- Product Design :
Manufacturing :
Materials :
Ecosystem :
- Covering topics such as design for long life and repair
Additive and subtractive techniques and localisation
Usage of recyclable materials rather than virgin
Repair or upgrade services to complement circular economy design

The outcome of the assement is a single figure rating by which product comparisons can be made. A TM66 score demonstrates a product’s performance in the context of a Circular Economy